



# COMMERCIAL POLYURETHANE PRODUCTS

Industry-Leading Energy Efficiency and Engineering


**HÖRMANN**



# Product Details

Steel Commercial Polyurethane Insulated Doors


WARRANTY INFORMATION



Door: 10 yr





Hardware: 1 yr



Springs: 1 yr

- **R-15.7** (440U) or **18.4** (450U)
- Steel Front and Back
- 1½" (440U) or 2" (450U) Sections
- 4 Colors + Custom Color
- 3 Window Designs




440U and 450U panels are produced in microgroove design with stucco embossment.



440U and 450U panels are also produced in flush design with woodgrain embossment.


## Window Design Options



- 1 Window 24" X 8"
- 2 Window 24" X 12"
- 3 Aluminum Full View

For the 440U and 450U, window frames (options 1 and 2) are available **standard in black** and **optional in white, brown, sandstone, grey** (to pair with silver metallic), and in custom color (Galaxy Paint System).

Full-view sections (option 3) may also be painted to match the door.



# Product Options

Commercial Polyurethane Insulated Doors - Unmatched Efficiency and Durability




OPTIONS KEY:  
 ● = Standard  
 ○ = Optional  
 - = Unavailable

Door Model	440U 1½" Sections	450U 2" Sections
Max Door Size	20'2" x 18'	26'2" x 18'
R-Value	15.7	18.4
Design Options	Microgroove Flush	Microgroove Flush
Texture	Stucco: Microgroove Wood Grain: Flush	Stucco: Microgroove Wood Grain: Flush
Color Options	White, Sandstone, Brown, Metallic Silver, Galaxy Paint	White, Sandstone, Brown, Metallic Silver, Galaxy Paint
<b>Glass Options</b>		
24x6 or 24x12 Black Frames	●	●
24x6 or 24x12 White, Brown, Sandstone, Grey (to pair with silver metallic), or Custom Color (Galaxy Paint System) Frames	○	○
Clear Anodized or Color-Matched Full-View Aluminum Sections	○	○
<b>Rope</b>		
	●	●
<b>Locks</b>		
Slide Lock	●	●
T-Handle	○	○
Cylinder	○	○
Mini-Warehouse	○	○
<b>Track Configuration</b>		
Bracket Mount	●	●
Continuous or Reverse Angle (per weight & width rules)	○	○
Tapered Angle (2")	○	○
3" Track	○	○
<b>Floor Seal</b>		
Grey 3" Vinyl Floor Seal	●	●
Black 4" Vinyl Floor Seal (shipped seperately)	○	○
<b>Hardware</b>		
14 ga. Hardware	●	●
11 ga. Hardware (end and center hinges) - consult factory	○	○

## ADDITIONAL OPTIONS

- Epoxy painted track and hardware
- 13 ball bearing sealed rollers 2" & 3"
- Higher Cycle Spring options: (25K, 50K & 100k)
- Optional Weather Seals: Vinyl Door Stop, Reverse angle jamb seal, header seal and bottom astragal standard & oversized

# Commercial Track Mounting Options



Typical Construction for Reverse Angle  
 Door Width = Door Opening Width + 2  
 (i.e. 8'2", 10'2", 16'2", 20'2" etc.)



# HÖRMANN NORTH AMERICA



Sparta, TN - North American Headquarters / Sectional Doors

## FIVE PRODUCTION PLANTS, ONE FAMILY



Puyallup, WA - Sectional Doors



Montgomery, IL - Sectional Doors



Barrie, ON (CAN) - High Performance Doors



Burgettstown, PA - High Performance Doors

As one of the world's leading manufacturers of doors we're committed to providing the best quality, value, and selection. Whether residential, commercial or industrial, we have the door you're looking for. Each Hörmann product gives you the perfect array of benefits and options to satisfy your customers.

### Call toll free

Eastern & Central US: 877.654.6762  
Western US: 800.522.2264  
Canada: 833.743.2443

### Contact

Email: [info@hormann.us](mailto:info@hormann.us)  
Website: [hormann.us](http://hormann.us)

### Follow us on social media



### AVAILABLE FROM:

